

- For indoor LED applications
- Can be used for installation in lights or as Independent LED-driver
- For luminaires of protection class I and protection class II



Model	AW01-0025	AW01-0047	AW01-0021	AW01-0011	AW01-0022	AW01-0020	
Item No.:	11868	11870	11876	11886	11889	13508	
Input voltage	220 - 240 V	220 - 240 V	220 - 240 V	220 - 240 V	220 - 240 V	220 - 240 V	
Input frequency	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	50 - 60 Hz	
Power factor	> 0.6	> 0.6	> 0.6	> 0.95	> 0.95	> 0.95	
Efficiency	> 76 %	> 78 %	> 82 %	> 86 %	> 84 %	> 85 %	
Constant current mode	Current	700 mA	-	1.8 A	350 mA	2.5 A	1.3 A
	Voltage (DC)	3 – 14.5 V	-	3 - 11 V	20 – 100 V	3 - 11 V	6 - 18 V
Constant voltage mode	Current (max.)	670 mA	1.25 A	1.67 A	-	2.5 A	1.25 A
	Voltage (DC)	15 V	12 V	12 V	-	12 V	24 V
Output power (max.)	10 W	15 W	20 W	30 W	30 W	30 W	
Idle voltage (max.) ¹⁾	16 V	12 V	12,5 V	115 V	12,5 V	25 V	
Ambient temperature <i>t_a</i> (max.)	40 °C	50 °C	40 °C	50 °C	50 °C	50 °C	
Case temperature <i>t_c</i> (max.)	85 °C	85 °C	75 °C	80 °C	85 °C	80 °C	
Dimension (LxWxH)	122 x 39 x 18 mm	122 x 39 x 18 mm	126 x 42.5 x 21.5 mm	137 x 42.5 x 27.5 mm	137 x 42.5 x 27.5 mm	137 x 42.5 x 27.5 mm	
Case type	A	A	B	C	C	C	
Weight	62 g	65 g	104 g	121 g	152 g	145 g	

¹⁾ The drivers are not approved for idle operation.

